



# HAKKEN DRILLS

The **BEST** drilling tools package starts here **Japanese Technology**

- Spindle thread size 1 1/4"-7 (industry standard)
- Motor comes with slip clutch that can be easily adjusted from outside the motor
- 4 adjustable leveling screws for drilling uneven surfaces
- Double insulated construction
- Water valve swivels 360 degrees
- Engineered for both vertical and horizontal drilling
- Light weight drill is easy to carry and lift for wall drilling
- Roller slide carriage provides smooth drilling with low friction
- One-year limited warranty



## SMD08

Power	120V
Rated Current	15A
Max Output	2.4kw (3.2HP)
Max Bit Capacity	8"
Spindle Thread	1-1/4"-7
Column Thickness	1-15/16"
Stand Height	31-7/8"
Carriage Travel	19-7/8"
Anchor Base	7" W x 8.5" L
Clutch Type	Slip
Speed	700 RPM (No Load)
Weight	41 lbs. (18.5kg)



## SMD12

Power	120V
Rated Current	20A
Max Output	2.4kw (3.2HP)
Max Bit Capacity	12"
Spindle Thread	1-1/4"-7
Column Thickness	2-5/16"
Stand Height	39-3/8"
Carriage Travel	24-3/8"
Anchor Base	7.5" W x 10" L
Clutch Type	Slip
Speed	400/950 RPM (No Load)
Weight	63 lbs. (28.4 kg)



## SMD16

Power	120V
Rated Current	20A
Max Output	2.4kw (3.2HP)
Max Bit Capacity	16" (with spacer)
Spindle Thread	1-1/4"-7
Column Thickness	2-5/16"
Stand Height	39-3/8"
Carriage Travel	24-3/8"
Anchor Base	7.5" W x 10" L
Clutch Type	Slip
Speed	400/950 RPM (No Load)
Weight	63 lbs. (28.4 kg)



## SMD24


Power	230V, 15.8A drill motor
Max Bit Capacity	24"
Spindle Thread	1-1/4"-7
Column Thickness	2-5/16"
Stand Height	57"
Carriage Travel	23-5/16", Standard pole base 38", Swivel pole base
Anchor Base	7-7/8" W x 12-1/2" L
Clutch Type	Slip
Speed	100/200 RPM
Weight	102 lbs. (46.3kg), Standard pole base 122 lbs. (55.3kg), Swivel pole base

### ADDITIONAL ACCESSORIES




#### STANDARD STAND

Lightweight standard pole base



#### STANDARD WITH LARGE VACUUM BASE

Including vacuum/anchor combination pad with wheels for mobility  
\*vacuum pump not included



#### ANGLED STAND

Gear type angle adjustable base of maximum of 120 degrees tilt



#### SWIVEL STAND

Extra sub column attached, which can be rotated 360° for easier extraction of long cores



#### DUSTLESS CONNECTOR

Available for all sizes



#### AUTO FEED SYSTEM

**NEW**